

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name : DENSURF DA 416  
Type of product : Polycarboxylic acid salt and amine derivatives

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Main use category : Industrial use  
Use of the substance/mixture : Dispersion agent

### 1.3. Details of the supplier of the safety data sheet

DENGE KİMYA VE TEKSTİL SAN. TİC. A.Ş.  
Velimeşe Organize Sanayi Bölgesi Mah.  
259.Sok. No:4/1  
Ergene TEKİRDAĞ TÜRKİYE  
T +90 (0282) 674 54 00 - F +90 (0282) 674 50 01  
[dercan@dengekimya.com](mailto:dercan@dengekimya.com) - [www.densurf.com](http://www.densurf.com)

### 1.4. Emergency telephone number

No additional information available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Specific target organ toxicity – Repeated exposure, Category 2	H373

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. Causes serious eye damage.

### 2.2. Label elements

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Hazard pictograms (SEA) :



Signal word (SEA) :

Hazardous ingredients : xylene; Ethylbenzene; Isobutanol

Hazard statements (SEA) : H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H332 - Harmful if inhaled.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (SEA)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/igniting material. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face with soap and water thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - IF ON SKIN: Wash with plenty of water/... P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately dial 114 for the NATIONAL POISON CENTER or call a doctor/physician. P312 - If you feel unwell, dial 114 for the NATIONAL POISON CENTER or call a doctor/physician. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P370+P378 - In case of fire: Use ... to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
--------------------------------	---

### 2.3. Other hazards

#### Other hazards not contributing to the classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.
Polyamine amide salt	-	50 – 100	Skin Irrit. 2, H315
xylene substance with national workplace exposure limit(s) (TR)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Ethylbenzene substance with national workplace exposure limit(s) (TR)	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	10 – 19,7	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Isobutanol	CAS-No.: 78-83-1 EC-No.: 201-148-0 EC Index-No.: 603-108-00-1	3 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell. If medical advice is needed, have product container or label at hand. If you feel unwell, seek medical advice (show the label where possible). Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: Call a poison center or a doctor if you feel unwell. If experiencing respiratory symptoms: Call a poison center or a doctor. Remove person to fresh air and keep comfortable for breathing. Allow the victim to rest.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Do not remove clothing if it sticks to the skin. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Obtain medical attention if pain, blinking or redness persists. Consult an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth out with water. If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting/risk of damage to lungs exceeds poisoning risk. Do not induce vomiting. Give nothing or a little water to drink. Go into open air and ventilate suspected area. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

- Precautionary measures fire : Evacuate area. Do not allow contact with air. Keep container tightly closed and away from heat, sparks and flame. Keep container closed when not in use. Local exhaust is needed at source of dust. Keep away from combustible materials.  
Firefighting instructions : In case of fire: stop leak if safe to do so. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Fight fire from a safe distance or use hoses with support or cannon engine. Prevent fire fighting water from entering the environment.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.  
Other information : On exposure to high temperature, may decompose, releasing toxic gases.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Avoid contact with skin and eyes. Do not handle until all safety precautions have been read and understood. Stop leak if safe to do so. Absorb spillage to prevent material damage. Isolate from fire, if possible, without unnecessary risk. Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Avoid contact with skin, eyes and clothing. Evacuate unnecessary personnel. Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Wear recommended personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so. Use grounded electrical/mechanical equipment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent liquid from entering sewers, watercourses, underground or low areas. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Consult an expert on waste disposal or treatment. Do not touch or walk on the spilled product. Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Collect spillage. Using a clean shovel, put the material in a dry container and cover without compressing it. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

- Methods for cleaning up : Notify authorities if product enters sewers or public waters. If the product is liquid. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). If the product is solid. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
- Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Remove contaminated clothes.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Comply with applicable regulations. Take precautionary measures against static discharge.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a closed container. Protect from moisture. Keep only in original container.
- Incompatible products : Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.
- Incompatible materials : For further information, refer to section 10 : "Stability and Reactivity".
- Storage area : Store away from heat. Store in a well-ventilated place.
- Packaging materials : Keep only in the original container in a cool, well-ventilated place away from combustible materials.

#### 7.3. Specific end use(s)

No additional information available





### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>xylene (1330-20-7)</b>	
<b>Turkey - Occupational Exposure Limits</b>	
Local name	Ksilen
OEL TWA	221 mg/m <sup>3</sup> (karışım izomerleri, saf)
OEL TWA [ppm]	50 ppm (karışım izomerleri, saf)
OEL STEL	442 mg/m <sup>3</sup> (karışım izomerleri, saf)
OEL STEL [ppm]	100 ppm (karışım izomerleri, saf)
Comments	Deri

<b>xylene (1330-20-7)</b>	
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete
<b>Ethylbenzene (100-41-4)</b>	
<b>Turkey - Occupational Exposure Limits</b>	
Local name	Etilbenzen
OEL TWA	442 mg/m <sup>3</sup>
OEL TWA [ppm]	100 ppm
OEL STEL	884 mg/m <sup>3</sup>
OEL STEL [ppm]	200 ppm
Comments	Deri
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

## 8.2. Exposure controls

Appropriate engineering controls	: Measure concentrations regularly, and at the time of any change occurring in conditions likely to have consequences on workers exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure that there is a suitable ventilation system.
Personal protective equipment	: Gloves. ISO 374-1. Protective goggles. ISO 16321-1. Dust formation: dust mask. Insulated gloves. Protective clothing.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.
Personal protective equipment symbol(s)	
   	
Environmental exposure controls	: Avoid release to the environment.
Consumer exposure controls	: The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, brownish liquid.
Colour	: Brownish
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available

Decomposition temperature	: No data available
Flammability	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

Solid content,% (105 °C, 2h)	: 49-53
Ionic Structure	: No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:dust,mist: Harmful if inhaled.

ATE (SEA) (dust, mist)	3,018 mg/l/4h
------------------------	---------------

<b>xylene (1330-20-7)</b>	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:

<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

<b>Isobutanol (78-83-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

<b>xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

<b>Ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>Isobutanol (78-83-1)</b>	
NOAEL (oral, rat, 90 days)	> 1450 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>xylene (1330-20-7)</b>	
EC50 - Crustacea [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3,16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

<b>Ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5,1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4,9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3,6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7,7 mg/l Test organisms (species): Skeletonema costatum



<b>Ethylbenzene (100-41-4)</b>	
LOEC (chronic)	1,7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0,96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
<b>Isobutanol (78-83-1)</b>	
LC50 - Fish [1]	1430 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1100 mg/l Test organisms (species): Daphnia pulex
NOEC (chronic)	20 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>DENSURF DA 416</b>	
Bioaccumulative potential	No additional information available

### 12.4. Mobility in soil

<b>DENSURF DA 416</b>	
Mobility in soil	No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015.

Waste treatment methods : Assure that emissions are compliant with all applicable air pollution control regulations.  
Dispose of contents/container in accordance with licensed collector's sorting instructions.






Product/Packaging disposal recommendations : Avoid release to the environment.

Additional information : Flammable vapours may accumulate in the container. Consult an expert on waste disposal or treatment. Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1993	1993	1993	1993	1993

ADR	IMDG	IATA	ADN	RID
<b>14.2. UN proper shipping name</b>				
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.
<b>Transport document description</b>				
UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III	UN 1993 Flammable liquid, n.o.s., 3, III	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

**14.6. Special precautions for user**

**Overland transport**

- Classification code (ADR) : F1
- Special provisions (ADR) : 274, 601
- Limited quantities (ADR) : 5I
- Excepted quantities (ADR) : E1
- Packing instructions (ADR) : P001, IBC03, LP01, R001
- Mixed packing provisions (ADR) : MP19
- Portable tank and bulk container instructions (ADR) : T4
- Portable tank and bulk container special provisions (ADR) : TP1, TP29
- Tank code (ADR) : LGBF
- Vehicle for tank carriage : FL
- Transport category (ADR) : 3
- Special provisions for carriage - Packages (ADR) : V12
- Special provisions for carriage - Operation (ADR) : S2
- Hazard identification number (Kemler No.) : 30
- Orange plates :



Tunnel restriction code (ADR) : D/E

**Transport by sea**

- Special provisions (IMDG) : 223, 274, 955
- Limited quantities (IMDG) : 5 L
- Excepted quantities (IMDG) : E1
- Packing instructions (IMDG) : LP01, P001
- IBC packing instructions (IMDG) : IBC03
- Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : A

**Air transport**

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3L

**Inland waterway transport**

Classification code (ADN) : F1  
Special provisions (ADN) : 274, 601  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 0

**Rail transport**

Classification code (RID) : F1  
Special provisions (RID) : 274, 601  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P001, IBC03, LP01, R001  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP29  
Tank codes for RID tanks (RID) : LGBF  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W12  
Colis express (express parcels) (RID) : CE4  
Hazard identification number (RID) : 30

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.1.1. National regulations**

Local regulations (Turkey) :

- : Regulation on Transportation of Dangerous Goods by Road published in the Official Journal numbered 28801 on October 24, 2013
- Personal Protective Equipment Regulation published in the Official Journal numbered 30761 on May 1, 2019
- Regulation on Use of Personal Protective Equipments in Workplaces published in the Official Journal numbered 28695 on July 2, 2013
- Occupational Health and Safety Regulation published in the Official Journal numbered 25311 on December 9, 2003
- Regulation on Test Methods that will be Applied to Determine the Physicochemical, Toxicological and Ecotoxicological Properties of Substances and Mixtures published in the Official Journal numbered 28848 on December 11, 2013
- Regulation on Health and Safety Precautions When Working with Chemical Substances published in the Official Journal numbered 28733 on August 12, 2013
- Regulation on Health and Safety Precautions When Working with Carcinogenic and Mutagenic Substances published in the Official Journal numbered 28730 on August 6, 2013 according to By-law on Registration, Evaluation, Authorization and Restriction of Chemicals (O.G: 23.06.2017 - 30105)
- Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015
- Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

This product doesn't contain any substances that is controlled or prohibited for use according to the Regulation on Ozone Depleting Substances published in the Official Journal numbered 30031 on April 7, 2017.

Substance(s) are not subject to Regulation on Persistent Organic Pollutants (O.G. 14.11.2018-30595)

**SECTION 16: Other information**

<b>Abbreviations and acronyms</b>	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association

<b>Abbreviations and acronyms</b>	
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative

Data sources : ECHA (European Chemicals Agency). Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

<b>Full text of H- and EUH-statements</b>	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.

<b>Full text of H- and EUH-statements</b>	
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

<b>Safety Data Sheet author's</b>	
Name	DEREN ERCAN
Certificate number	LONCA KDU 81/2021.26
Certificate valid until	14/10/2026
Contact information	dercan@dengekimya.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.