

SDS TR reference: SDS.158 Issue date: 02.08.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1. Product identifier**

Product form Product name Type of product : Mixture : DENSURF AF 250

: Mixture of hydrocarbons

#### **1.2.** Relevant identified uses of the substance or mixture and uses advised against

Main use category Use of the substance/mixture : Industrial use

: It is effective in removing macro and micro foams in solvent and solventless systems.

#### 1.3. Details of the supplier of the safety data sheet

DENGE KİMYA VE TEKSTİL SAN. TİC. A.Ş. Velimeşe Organize Sanayi Bölgesi Mah. 259.Sok. No:4/1 Ergene TEKİRDAĞ TÜRKİYE T +90 (0282) 674 54 00 - F +90 (0282) 674 50 01 <u>dercan@dengekimya.com</u> - <u>www.densurf.com</u>

1.4. Emergency telephone number

No additional information available

#### **SECTION 2: Hazards identification**

Adverse physicochemical, human health and

#### 2.1. Classification of the substance or mixture

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Flammable liquids, Category 3	H226
Carcinogenicity, Category 2	H351
Specific target organ toxicity - Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H-statements: see section 16	

: Suspected of causing cancer. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

environmental effects

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Hazard pictograms (SEA)	
	GHS02 GHS07 GHS08 GHS09
Signal word (SEA)	: Warning
Hazardous ingredients	: Hydrocarbon
Hazard statements (SEA)	: H226 - Flammable liquid and vapour.
	H336 - May cause drowsiness or dizziness.
	H351 - Suspected of causing cancer.
	H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (SEA)	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.



SDS TR reference: SDS.158 Issue date: 02.08.2023

> P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/igniting material. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 - If exposed or concerned, get medical advice and attention. P312 - If you feel unwell, dial 114 for the NATIONAL POISON CENTER or call a doctor/physician. P370+P378 - In case of fire: Use ... to extinguish. P391 - Collect spillage. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards

#### Other hazards not contributing to the classification

No additional information available

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.
Hydrocarbon	EC-No.: 919-284-0	95 – 99	Carc. 2, H351 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Silicone	-	≤ 1,8	Flam. Liq. 3, H226
xylene	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	≤ 0,7	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Ethylbenzene substance with national workplace exposure limit(s) (TR)	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	≤ 0,168	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-statements: see section 16



SDS TR reference: SDS.158 Issue date: 02.08.2023

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention. If medical advice is needed, have product container or label at hand. If you feel unwell, seek medical advice (show the label where possible). Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product.
First-aid measures after inhalation	: If experiencing respiratory symptoms: Call a poison center or a doctor. Remove person to fresh air and keep comfortable for breathing. Allow the victim to rest.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Do not remove clothing if it sticks to the skin. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists. Consult an ophtalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and eff	ects, both acute and delayed
Symptoms/effects	: May cause drowsiness or dizziness.
4.3. Indication of any immediate medical attention and special treatment needed	

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	<ul><li>Water spray. Dry powder. Foam. Carbon dioxide.</li><li>Do not use a heavy water stream.</li></ul>
5.2. Special hazards arising from the subst	tance or mixture
Hazardous decomposition products in case of fire	: Toxic fumes may be released.
5.3. Advice for firefighters	
Precautionary measures fire	: Do not allow contact with air. Keep container tightly closed and away from heat, sparks and flame. Keep container closed when not in use.
Firefighting instructions	: In case of fire: stop leak if safe to do so. Cool laterally with water containers exposed to flames, even after the fire is extinguished. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: On exposure to high temperature, may decompose, releasing toxic gases.

6.1. Personal precautions, prote	ective equipment and emergency procedures
General measures	: Evacuate area. Avoid contact with skin and eyes. Do not handle until all safety precautions have been read and understood. Stop leak if safe to do so. Absorb spillage to prevent material damage. Isolate from fire, if possible, without unnecessary risk. No open flames. No smoking.

**SECTION 6: Accidental release measures** 



SDS TR reference: SDS.158

ssue	date:	02.08	.2023	

6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing. Evacuate unnecessary personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. Wear recommended personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so. Use grounded electrical/mechanical equipment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent liquid from entering sewers, watercourses, underground or low areas. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up		
For containment	: Collect spillage. Consult an expert on waste disposal or treatment. Do not touch or walk on the spilled product. Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Using a clean shovel, put the material in a dry container and cover without compressing it. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.	
Methods for cleaning up	Notify authorities if product enters sewers or public waters. If the product is liquid. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). If the product is solid. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.	
Other information	: Dispose of materials or solid residues at an authorized site.	
6.4. Reference to other sections		

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	<ul> <li>Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>Do not eat, drink or smoke when using this product. Always wash hands after handling the</li> </ul>
7.2. Conditions for safe storage, including	product. Remove contaminated clothes. g any incompatibilities
Technical measures	: Store in a well-ventilated place. Keep container tightly closed. Comply with applicable
	regulations. Take precautionary measures against static discharge.
Storage conditions	Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a closed container. Protect from moisture. Keep only in original container.
Incompatible products	: Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.
Incompatible materials	: For further information, refer to section 10 : "Stability and Reactivity".
Storage area	: Store away from heat. Store in a well-ventilated place.
Packaging materials	: Keep only in the original container in a cool, well-ventilated place away from combustible materials.



SDS TR reference: SDS.158 Issue date: 02.08.2023

#### 7.3. Specific end use(s)

No additional information available

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

xylene (1330-20-7)		
Turkey - Occupational Exposure Limits		
Local name	Ksilen	
OEL TWA	221 mg/m³ (karışım izomerleri, saf)	
OEL TWA [ppm]	50 ppm (karışım izomerleri, saf)	
OEL STEL	442 mg/m³ (karışım izomerleri, saf)	
OEL STEL [ppm]	100 ppm (karışım izomerleri, saf)	
Comments	Deri	
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete	
Ethylbenzene (100-41-4)		
Turkey - Occupational Exposure Limits		
Local name	Etilbenzen	
OEL TWA	442 mg/m <sup>3</sup>	
OEL TWA [ppm]	100 ppm	
OEL STEL	884 mg/m³	
OEL STEL [ppm]	200 ppm	
Comments	Deri	
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete	

#### 8.2. Exposure controls

Appropriate engineering controls	: Measure concentrations regularly, and at the time of any change occuring in conditions likely to have consequences on workers exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure that there is a suitable ventilation system.
Personal protective equipment	: Gloves. Protective goggles. Wear a mask. Protective clothing.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment
Personal protective equipment symbol(s)	

Environmental exposure controls

: Avoid release to the environment.



SDS TR reference: SDS.158 Issue date: 02.08.2023

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Physical state	: Liquid
Appearance	: Colorless, clear liquid
Colour	: Colourless
Odour	: odourless
Odour threshold	: No data available
рН	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 0,894±0,02 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

Ionic Structire

: Nonionic

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

**10.3.** Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

**10.6. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



SDS TR reference: SDS.158 Issue date: 02.08.2023

SECTION 11: Toxicological infor	mation
11.1. Information on toxicological e	ffects
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified
Hydrocarbon	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat [ppm]	> 4688 ppm
xylene (1330-20-7)	<u>ł</u>
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
Ethylbenzene (100-41-4)	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
Hydrocarbon	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90- Day Oral Toxicity)
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28- Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

# **SECTION 12: Ecological information**

12.1. Toxicity	
Ecology - general Hazardous to the aquatic environment, short-term (acute)	<ul><li>Toxic to aquatic life with long lasting effects.</li><li>Not classified</li></ul>
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Hydrocarbon	
LC50 - Fish [1]	2 – 5 mg/l



SDS TR reference: SDS.158 Issue date: 02.08.2023

Hydrocarbon	
EC50 - Crustacea [1]	3 – 10 mg/l
xylene (1330-20-7)	
EC50 - Crustacea [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3,16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	5,1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4,9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3,6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7,7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1,7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0,96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
12.2. Persistence and degradability	y .
Hydrocarbon	
Biodegradation	60,74 %
12.3. Bioaccumulative potential	
DENSURF AF 250	
Bioaccumulative potential	No additional information available
12.4 Mobility in soil	

# 12.4. Mobility in soil

DENSURF AF 250	
Mobility in soil	No additional information available

# 12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects	
Ozone	: Not classified
Other adverse effects	: No additional information available

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Regional legislation (waste)	<ul> <li>Disposal must be done according to official regulations.</li> <li>Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015.</li> </ul>



SDS TR reference: SDS.158 Issue date: 02.08.2023

# Waste treatment methods: Assure that emissions are compliant with all applicable air pollution control regulations.<br/>Dispose of contents/container in accordance with licensed collector's sorting instructions.Product/Packaging disposal recommendations<br/>Additional information: Avoid release to the environment.<br/>: Consult an expert on waste disposal or treatment. Do not re-use empty containers.

SECTION 14: Transport information

#### In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number				
1993	1993	1993	1993	1993
14.2. UN proper shippin	g name			
FLAMMABLE LIQUID, N.O.S. (Hydrocarbon)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbon)	Flammable liquid, n.o.s. (Hydrocarbon)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbon)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbon)
Transport document descr	iption			
UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbon), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbon), 3, III, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1993 Flammable liquid, n.o.s. (Hydrocarbon), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbon), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbon), 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard o	class(es)			
3	3	3	3	3
14.4. Packing group				
III	III	111	III	III
14.5. Environmental haz	ards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
environment: Yes No supplementary informatio	Marine pollutant: Yes	environment: Yes	environment:	Yes

#### 14.6. Special precautions for user

	Overland transport Classification code (ADR)		F1
S	Special provisions (ADR)	:	274, 601
L	imited quantities (ADR)	:	51
E	Excepted quantities (ADR)	:	E1
F	Packing instructions (ADR)	:	P001, IBC03, LP01, R001
Ν	lixed packing provisions (ADR)	:	MP19
F	Portable tank and bulk container instructions (ADR)	:	Τ4
F	Portable tank and bulk container special provisions	:	TP1, TP29
(	ADR)		
Т	ank code (ADR)	:	LGBF
V	ehicle for tank carriage	:	FL
Т	ransport category (ADR)	:	3



SDS TR reference: SDS.158 Issue date: 02.08.2023

:

:

:

Special provisions for carriage - Packages (ADR) Special provisions for carriage - Operation (ADR) Hazard identification number (Kemler No.) Orange plates

Tunnel restriction code (ADR)

# Transport by sea

Transport by sea	
Special provisions (IMDG)	: 223, 274, 955
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Air transport	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L
Inland waterway transport	
Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601
Limited quantities (ADN)	: 5 L

Excepted quantities (ADN) : E1 : T Carriage permitted (ADN) Equipment required (ADN) : PP, EX, A Ventilation (ADN) : VE01 Number of blue cones/lights (ADN) : 0

: V12 : S2 30 30 1993 D/E



SDS TR reference: SDS.158 Issue date: 02.08.2023

Rail transport		
Classification code (RID)	:	F1
Special provisions (RID)	:	274, 601
Limited quantities (RID)	:	5L
Excepted quantities (RID)	:	E1
Packing instructions (RID)	:	P001, IBC03, LP01, R001
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	Τ4
Portable tank and bulk container special provisions	:	TP1, TP29
(RID)		
Tank codes for RID tanks (RID)	:	LGBF
Transport category (RID)	:	3
Special provisions for carriage – Packages (RID)	:	W12
Colis express (express parcels) (RID)	:	CE4
Hazard identification number (RID)	:	30

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

AF A Ontote bankle	and a subsequence of a loss	and a diama file site is diama		
15.1. Safety, nealth	and environmental re	gulations/legislation	specific for the substanc	e or mixture

#### 15.1.1. National regulations

·····	
Local regulations (Turkey)	<ul> <li>Regulation on Transportation of Dangerous Goods by Road published in the Official Journal numbered 28801 on October 24, 2013         Personal Protective Equipment Regulation published in the Official Journal numbered 30761 on May 1, 2019         Regulation on Use of Personal Protective Equipments in Workplaces published in the Official Journal numbered 28695 on July 2, 2013         Occupational Health and Safety Regulation published in the Official Journal numbered 28311 on December 9, 2003         Regulation on Test Methods that will be Applied to Determine the Physicochemical, Toxicological and Ecotoxicological Properties of Substances and Mixtures published in the Official Journal numbered 28848 on December 11, 2013         Regulation on Health and Safety Precautions When Working with Chemical Substances published in the Official Journal numbered 28733 on August 12, 2013         Regulation on Health and Safety Precautions When Working with Carcinogenic and Mutagenic Substances published in the Official Journal numbered 28733 on August 12, 2013         Regulation on Health and Safety Precautions, Authorization and Restriction of Chemicals (O.G: 23.06.2017 - 30105)         Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015         Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.</li></ul>

This product doesn't contain any substances that is controlled or prohibited for use according to the Regulation on Ozone Depleting Substances published in the Official Journal numbered 30031 on April 7, 2017.

Substance(s) are not subject to Regulation on Persistent Organic Pollutants (O.G. 14.11.2018-30595)

# **SECTION 16: Other information**

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road



SDS TR reference: SDS.158 Issue date: 02.08.2023

Abbreviations a	Abbreviations and acronyms		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
ΙΑΤΑ	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
РВТ	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		

Data sources

: ECHA (European Chemicals Agency). Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.



SDS TR reference: SDS.158 Issue date: 02.08.2023

Full text of H- and EUH-statements		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Carc. 2	Carcinogenicity, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	

Safety Data Sheet author's		
Name	DEREN ERCAN	
Certificate number	LONCA KDU 81/2021.26	
Certificate valid until	14/10/2026	
Contact information	dercan@dengekimya.com	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.